


ALULED-II-HLO-IP40-C

LED MODULES
IN FLAT ALUMINIUM PROFILE
WITH HIGH LUMEN OUTPUT



ALULED-II-HLO-IP40-C

AluLED-II-HLO-IP40-C is ideal for indoor protected applications. The slim and flat design is extremely flexible for low profile lighting design mounting.

A key advantage of AluLED is the extremely slim and flat design, which makes it suitable for illuminating complex structures or places where space is too limited to permit traditional light sources to be installed.

Typical applications

- Indoor contour illumination
- Indoor facility lighting



ALULED-II-HLO-IP40-C




- **ALUMINIUM PROFILE WITH HIGH QUALITY LEDs**
- **PLUG & PLAY DUE TO PRE-WIRED CONNECTORS**
- **SUITABLE FOR INDOOR APPLICATIONS**
- **SLIM AND FLAT DESIGN**
- **INTEGRATED HEAT SINK FOR OPTIMAL THERMAL MANAGEMENT**
- **5 YEARS WARRANTY**
Further infos see www.vossloh-schwabe.com
- **MADE IN GERMANY**



AluLED-II-HLO-IP40-C

Technical notes

Voltage supply: 24 V DC
 Beam angle: 120°
 Allowed ambient temperature t_a : -20 to 65 °C
 Allowed storage temperature: -40 to 85 °C
 Degree of protection: IP40
 ESD protection up to 2kV
 Maximum bridging current load: 3 A
 Lumen maintenance:
 L90/B10: > 50,000 hrs. at $t_p/t_c = 65$ °C
 L70/B10: > 50,000 hrs. at $t_p/t_c = 80$ °C
 Packaging unit: 20 pcs. including mounting clips (brackets) and screws



Optical characteristics

at $t_p = 50$ °C

Type	Ref. No.	Length mm	No. of LEDs	Current mA	Colour	Colour temperature (K)	Luminous flux* lm	Power W	Cover
White modules									
AluLED-320-HLO-4000-II-IP40-C	145281	320	28	269	neutral white	4000 ± 300	603	6.5	Clear
AluLED-920-HLO-4000-II-IP40-C	608136	920	84	807	neutral white	4000 ± 300	1809	19.8	Clear
AluLED-1220-4000-HLO-II-IP40-C	608454	1220	112	1076	neutral white	4000 ± 300	2412	26.4	Clear

* Production tolerance for luminous flux: $\pm 10\%$

Customised lengths 170mm – 1520mm, available on request.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.

AluLED-II-HLO-IP40-C

EasyConnect Cable for AluLED

Max. permissible current: 3 A

Number of strands: 2/4

(Strand diameter: 0.35 mm²/22 AWG)


For monochrome modules with 2 strands

Ref. No.: 543426 25 cm, feed cable for power supply

Ref. No.: 543427 50 cm, PCB to PCB connector For RGB modules with 4 strands

Ref. No.: 543428 25 cm, feed cable for power supply

Ref. No.: 543429 50 cm, PCB to PCB connector



Shrink caps

For sealing exposed connection wires

(Strand diameter: 0.35 mm²/22 AWG)

Adhesive coating on the inside

Ref. No.: 571150 transparent

Ref. No.: 571151 black

Magnetic holder for AluLED

For easy fixation with springs and magnet

(scope of supply: 2 pcs.)

Ref. No.: 143208




Safety Instructions

- AluLED products may only be installed and commissioned by authorised and qualified staff.
- Please read these instructions carefully prior to installing and commissioning the system since this is the only way to ensure safe and proper system operation. You are recommended to keep these instructions in a safe place for possible future reference.
- Any work undertaken on a device must only be performed after disconnection from the mains.
- Relevant safety and accident prevention measures must be observed.
- Products must never be improperly opened since electrical voltage poses a risk to life. Repairs must only be performed by the manufacturer.
- Connecting feeder/supply lines to external voltage, e.g. 230 V mains voltage, can destroy individual system components.

Mounting

1. Screw the mounting clips firmly to the substrate.
 2. Click module into the mounting clips.
- Mounting clips (brackets) are used to attach AluLED-II-HLO-IP40-C modules to a solid, load-bearing substrate. The mounting clips must be attached to the substrate using screws. The space left between the mounting clips must ensure the module neither bends nor bows. Once properly mounted, the AluLED-II-HLO-IP40-C module must be firmly enclosed by the mounting clips.
 - The module can be installed any way up, but vertical wall mounting could lead to the module slipping out of the clips.
 - Sufficient clearance must be left to other neighbouring objects to allow for the longitudinal thermal expansion of the module.
 - To prevent corrosion, contact with base metals, aggressive fluids and gases must be avoided. Operation in environments that are chemically enriched with (aggressive) chemical substances can impair functionality and can even result in total module failure. Detailed information as well as examples of hazardous environments and chemical substances can be found in the document "Chemical Incompatibilities Affecting LEDs", published by Vossloh-Schwabe Deutschland (www.vossloh-schwabe.com).



The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.

AluLED-II-HLO-IP40-C

Installation Instructions

1. When using several modules, the connector of a feed-out line must be attached to the connector of the following module's feed-in line.
 2. The final feed-out line must be protected against humidity and water ingress with a connector.
 3. Operation only with power supply units that feature the following protection:
 - Short-circuit protection
 - Overload protection
 - Overheating protection
 - SELV (Safety Extra Low Voltage)
 4. Check the polarity of the control gear's feed-in line (red + /black -).
 5. Attach the control gear's feed-in line to the connector of the (first) AluLED-II-HLO-IP40-C module's feed-in line.
 6. Calculate the total power uptake of the connected AluLED-II-HLO-IP40-C modules and compare the value with the data supplied for the connected control gear. Should the control gear's permissible total power uptake be exceeded, the equipment needs to be replaced with an adequately rated control gear unit.
 7. Connect the control gear to the power supply in accordance with the installation instructions.
- Each AluLED-II-HLO-IP40-C module is fitted with a pre-assembled feed-in line with a connecting terminal as well as with a feed-out line with a connector for looping the supply voltage through to the next AluLED-II-HLO-IP40-C module.
 - Should this not be necessary, the spare connector must be protected against the ingress of humidity.
 - Alternatively, the connecting terminal can be removed and the exposed connecting wires sealed using shrink caps that are internally coated with adhesive (Ref. No.: 571150 (transparent) or 571151 (black)).
 - If only one such shrink cap is used to seal both connecting wires, care must be taken to ensure the wires are of differing lengths to prevent the internal metal conductors from touching one another.
 - The connecting terminals and connectors of the pre-assembled connecting leads prevent any reversal of polarity. Only the polarity of the control gear's requisite feed-in line (Ref. No.: 543426) can be reversed when connecting it to the control gear.
 - Prior to commissioning, care must be taken to ensure the polarity of the control gear's feed-in line is correct. The red cable is "+" and the black cable is "-".
 - The maximum 3 A current load on the voltage supply line, the control gear's feed-in line and the extension lead must not be exceeded. The resulting maximum number of AluLED-II-HLO-IP40-C modules that can be connected is additionally dependent on the maximum output current of the 24 V constant voltage driver with a constant output voltage as well as the voltage drop caused by the AluLED-II-HLO-IP40-C modules and their leads.

Further Information

- If the distance between the control gear and the (first) AluLED-II-HLO-IP40-C module is too great to be bridged using the feed-in lines of the control gear and the AluLED-II-HLO-IP40-C module, a VS extension lead (Ref. No.: 543427) must be used to close the gap.
- Should an extension lead additionally be used to connect AluLED-II-HLO-IP40-C modules that are farther away, the unavoidable electrical resistance of the extension lead will cause a more pronounced voltage drop, which in turn can impair the functionality of the AluLED-II-HLO-IP40-C modules. AluLED-II-HLO-IP40-C modules are designed for operation with a constant voltage of 24 V.

Complies to following standards

EN 62031:2008 / A1:2013 / A2:2015
LED modules for general lighting – Safety specifications

EN 60529:1991 / A1:2000 / A2:2013
Degrees of protection provided by enclosures (IP Code)

EN 61547:2009
Electrostatic discharge immunity test (ESD):
4 kV direct contact discharge – 8 kV air discharge

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.